



**NOTES:**

1. IF CLEAN-OUT IS INSTALLED IN DRIVEWAY OR FOR 6" LATERALS, USE CHRISTY G5 TRAFFIC VALVE BOX WITH "SEWER" CAST IN LID (OR APPROVED EQUAL). BOX SHALL HAVE A CONCRETE COLLAR. (SEE DETAIL DS-6 FOR DETAILS OF CONCRETE COLLAR)
2. WHEN PROPERTY LINE IS AT BACK OF WALK, INSTALL CLEAN-OUT BEHIND BACK OF WALK.
3. PROVIDE STOPPER WHEN THERE IS NO ON-SITE LATERAL CONNECTION.
4. MATERIAL FOR THE CLEANOUT PIPE SHALL MATCH THE MATERIAL FOR THE LATERAL. SEE CITY'S SPECIFICATIONS FOR MATERIALS.
5. FOR 8" OR LARGER LATERALS, A STANDARD MANHOLE SHALL BE INSTALLED AT OR NEAR THE PROPERTY LINE.



DRAWN BY: K. TRAN  
 CHECKED BY: F. AMIN  
 APPROVED BY: G. GOMEZ  
 DATE: OCTOBER 2013

**4" & 6" SANITARY SEWER  
 CLEAN-OUT**

CITY OF SANTA CLARA

**SS-1**

PAGE: 37